


Engine Yanmar 3TNV80F-SSLY
Rated Power 13.4 kW (18 hp / 18.2 ps) @ 2,200 rpm
Maximum Dig Depth 2,290 mm (7'6")
Standard Bucket Capacity 0.045 m³ (0.06 yd³)
Operating Weight (with Cab) 1,900 kg (4,189 lbs)
Operating Weight (with Canopy) 1,800 kg (3,969 lbs)

## 9018F EXCAVATOR

## 9018F SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Tier 4F / Stage V
Make	Yanmar
Model	3TNV80F-SSLY
Rated Power	13.4 kW (18 hp / 18.2 ps) @ 2,200 rpm
Peak Torque	63.1~67.4 N·m (46.5~49.7 lbf·ft) @ 1,600 rpm
Number of Cylinders	3
Displacement	1.267 L

UNDERCARRIAGE	
Shoe Width	230 mm (9 in)
Number of Shoes per Side	37 (Metal) / 70 (Rubber)
Number of Bottom Rollers per Side	3



1070	
	2350
1230 1580	
3707	

BOOM & ARM	
Boom Length	1,685 mm (5'6")
Arm Length	1,070 mm (3'6")

## **BUCKET PERFORMANCE**

Std. Bucket Heaped Capacity (Referenced) 0.045 m³ (0.06 yd³)

TRACK DRIVE	
Maximum Travel Speed	4.5 km/h (2.8 mph)
Drawbar Pull	16 kN (3,597 lbf)

SERVICE CAPACITIES	
Fuel Tank	28 L (7.4 gal)
Engine Oil	4.4 L (1.2 gal)
Cooling System	3.3 L (0.9 gal)
Hydraulic Reservoir	24 L (6.3 gal)

HYDRAULIC SYSTEM	
Main Pumps Total Flow	55 L/min (14.5 gal/min)
Relief Pressure, main	21 MPa (3,046 psi)

SWING SYSTEM	
Swing Speed	9.5 rpm

WORKING RANGE	
A. Max. Digging Reach	3,910 mm (12'10")
B. Max. Digging Reach on Ground	3,850 mm (12'8")
C. Max. Digging Depth	2,290 mm (7'6")
D. Max. Digging Depth, 2.44 m (8') Level	1,820 mm (5'12")
E. Max. Cutting Height	3,385 mm (11'1")
F. Max. Dumping Height	2,370 mm (7'9")
G. Min. Front Swing Radius	1,660 mm (5'5")
Bucket Digging Force (ISO)	16 kN (3,597 lbf)
Arm Digging Force (ISO)	9 kN (2,023 lbf)

