

B230CBULLDOZER

B230C SPECIFICATIONS >>>

ENGINE	
Model	Cummins QSNT-C240
Type	EFI turbocharged, 4-stroke
Emission Regulation	Tier 3 / China III
Displacement	14 L
Max. Engine Speed	2,200 rpm
Engine Power	179 kW (240 hp / 243 ps) @ 2,000 rpm
Peak Torque	1,050 N·m @ 1,400 rpm
Lowest Fuel Consumption	≤217 g/kW·h
Start Motor	24V
Drawbar Pull	225 kN

UNDERCARRIAGE	
Туре	Splayed oscillating, equalizer suspension
Track Shoes (Each Side)	7
Top Idlers (Each Side)	2
Track Type	Single grouser
Shoe Width	560 mm
Track Shoes (Each Side)	39
Link Pitch	216 mm
Gradeability	30°
Ground Pressure	76 kpa

DIMENSIONS	
A Overall Length	5,500 mm
B Height to Top of Cab	3,380 mm
C Track Length on Ground	2,840 mm
D Blade Height	1,395 mm
E Blade Width	3,725 mm
F Width over Track	2,560 mm
G Track Gauge	2,000 mm

	A
- C	
→ A	

TRAVEL SPEED		
	Gear 1	0-3.8 km/h
Forward	Gear 2	0-6.9 km/h
0	Gear 3	0-12 km/h
Reverse	Gear 1	0-4.9 km/h
	Gear 2	0-8.6 km/h
	Gear 3	0-13.8 km/h

HYDRAULIC SYSTEM	
Flow	198 L/min
Pressure	19.5 MPa
Pump	Gear pump
Cylinders	Dual-acting piston type

DRIVE SYSTEM	
Torque Converter	Single-stage, single-phase three elements
Transmission	Planetary power shift
Clutch	Multiple - disc oil powder metallurgy disc compressed by spring, released by hydraulic.
Brakes	Oil two direction floating band brake operated by mechanical foot pedal.

