

17.0 m³

540 mm

26,800 kg 1,300 mm

179 kW (240 hp / 243 ps) @ 2,000 rpm **Engine Power Blade Capacity Operating Weight Lift above Ground Depth below Ground**

B230CR BULLDOZER

B230CR SPECIFICATIONS >>>

ENGINE	
Model	ChongQing Cummins QSNT-C240
Туре	Turbocharged
Emission Regulation	Tier 3/ China III
Displacement	14 L
Max. Engine Speed	2,200 rpm
Engine Power	179 kW (240 hp /243 ps) @ 2,000 rpm
Peak Torque	1,050 N·m @ 1,400 rpm
Lowest Fuel Consumption	≤ 217 g/kW·h
Start Motor	24 V
Drawbar Pull	225 kN

UNDERCARRIAGE	
Type	Splayed oscillating, equalizer suspension
Track Rollers (Each Side)	8
Top Idlers (Each Side)	2
Track Type	Triangle track shoe, swamp
Shoe Width	910 mm
Track Shoes (Each Side)	45
Link Pitch	216 mm
Gradeability	30°
Ground Pressure	39 kpa

DIMENSIONS	
A Overall Length	6,060 mm
B Height to Top of Cab	3,420 mm
C Track Length on Ground	3,480 mm
D Blade Height	1,990 mm
E Blade Width	4,365 mm
F Width over Track	3,160 mm
G Track Gauge	2,250 mm

TRAVEL SPEED		
Foward	Gear 1	0-3.8 km/h
	Gear 2	0-6.8 km/h
	Gear 3	0-10.7 km/h
Reverse	Gear 1	0-4.9 km/h
	Gear 2	0-8.6 km/h
	Gear 3	0-13.3 km/h

HYDRAULIC SYSTEM	
Flow	198 L/min
Pressure	19.5 MPa
Pump	Gear pump
Cylinders	Dual-acting piston type

DRIVE SYSTEM	
Torque Converter	Single-stage, single-phase three elements
Transmission	Planetary power shift
Clutch	Multiple-disc oil powder metallurgy disc compressed by spring, released by hydraulic
Brakes	Oil two direction floating band brake operated by mechanical foot pedal.



